



BEELED -

MODEL: 2504R1D-KPC-A



Features

- High efficiency
- Low Power consumption
- General purpose leads
- Selected minimum intensities
- Available on tape and reel
- Pb free

Descriptions

- The series is specially designed for applications requiring higher brightness
- The LED lamps are available with different colors, intensities, epoxy colors, etc
- Superior performance in outdoor environment

Usage Notes:

- Surge will damage the LED
- When using LED, it must use a protective resistor in series with DC current about 20mA

Applications

- Status indicators
- Commercial use
- Advertising Signs
- Back lighting


BEELED -

MODEL: 2504R1D-KPC-A

Device Selection Guide

LED Part No.	Chip		Lens Color
	Material	Emitted Color	
2504R1D-KPC-A	AlGaInP	Red	Diffused

Package Dimensions



Notes:

- Other dimensions are in millimeters, tolerance is 0.25mm except being specified.
- Protruded resin under flange is 1.5mm Max LED.
- Bare copper alloy is exposed at tie-bar portion after cutting.



BEELED -

MODEL: 2504R1D-KPC-A

Absolute Maximum Rating ($T_a=25^\circ C$)

Parameter	Symbol	Absolute Maximum Rating		Unit
Forward Pulse Current	I_{FPM}	100		mA
Forward Current	I_{FM}	30		mA
Reverse Voltage	V_R	5		V
Power Dissipation	P_D	140		mW
Operating Temperature	T_{opr}	-40~+80		°C
Storage Temperature	T_{stg}	-40~+100		°C
Soldering Heat (5s)	T_{sol}	260		°C

Electro-Optical Characteristics ($T_a=25^\circ C$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_v	50	---	100	mcd	IF=20mA(Note1)
Viewing Angle	$2\theta_{1/2}$	---	120	---	Deg	(Note 2)
Peak Emission Wavelength	λ_p	620	---	635	nm	IF=20mA
Spectral Line Half-Width	$\Delta\lambda$	15	20	25	nm	IF=20mA
Forward Voltage	V_F	1.9	---	2.3	V	IF=20mA
Reverse Current	I_R	---	---	10	μA	VR=5V







Note:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

BEELED -

MODEL: 2504R1D-KPC-A

Typical Electro-Optical Characteristics Curves





BEELED -

MODEL: 2504R1D-KPC-A

1. , BEELED
2. ,
BEELED ,
3. ,
BEELED , BEELED.