

BEELED

СВЕТОДИОДЫ BEELED - ТЕХНИЧЕСКОЕ ОПИСАНИЕ

MODEL: 5234G3C-ESB-A

Features

- High luminous intensity output
- Oval Shape
- Well defined spatial radiation
- Wide viewing angle($2\theta_{1/2}$):70° /30°
- UV resistant epoxy
- Pb free



Descriptions

- This precision optical performance oval LED is specifically designed for passenger information signs
- This lamp has matched radiation patterns with,Red
Or green color mixing color applications
- Superior performance in outdoor environment



Usage Notes:

- The ultra bright LED is an electrostatic insensitive device,so static electricity and surge will damage the LED.It is required to wear a wrist-band when handling the LED. All device, equipment,machinery, desk and ground must be properly grounded
- When using LED, it must use a protective resistor in series with DC current about 20mA

Applications

- Full color/video signs
- Message boards
- Variable message signs(VMS)
- Commercial outdoor advertising


СВЕТОДИОДЫ BEELED - ТЕХНИЧЕСКОЕ ОПИСАНИЕ

MODEL: 5234G3C-ESB-A

Device Selection Guide

LED Part No.	Chip		Lens Color
	Material	Emitted Color	
5234G3C-ESB-A	InGaN	Green	Water clear

Package Dimensions



Notes:

- Other dimensions are in millimeters, tolerance is 0.25mm except being specified.
- Protruded resin under flange is 1.5mm Max LED.
- Bare copper alloy is exposed at tie-bar portion after cutting.



СВЕТОДИОДЫ BEELED - ТЕХНИЧЕСКОЕ ОПИСАНИЕ

MODEL: 5234G3C-ESB-A

Absolute Maximum Rating ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Absolute Maximum Rating	Unit
Forward Pulse Current	I_{FPM}	70	mA
Forward Current	I_{FM}	30	mA
Reverse Voltage	V_{R}	5	V
Power Dissipation	P_{D}	140	mW
Operating Temperature	T_{opr}	$-40\sim+80$	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	$-40\sim+100$	$^{\circ}\text{C}$
Soldering Heat (5s)	T_{sol}	260	$^{\circ}\text{C}$

Electro-Optical Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_{v}	1800	---	2700	mcd	$I_{\text{F}}=20\text{mA}$ (Note1)
Viewing Angle	$2\theta_{1/2}$	---	X: 70° Y: 30°	---	Deg	(Note 2)
Peak Emission Wavelength	λ_{p}	520	---	530	nm	$I_{\text{F}}=20\text{mA}$
Spectral Line Half-Width	$\Delta\lambda$	30	35	40	nm	$I_{\text{F}}=20\text{mA}$
Forward Voltage	V_{F}	2.9	---	3.3	V	$I_{\text{F}}=20\text{mA}$
Reverse Current	I_{R}	---	---	10	μA	$V_{\text{R}}=5\text{V}$


Note:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

СВЕТОДИОДЫ BEELED - ТЕХНИЧЕСКОЕ ОПИСАНИЕ

MODEL: 5234G3C-ESB-A

Typical Electro-Optical Characteristics Curves





СВЕТОДИОДЫ BEELED - ТЕХНИЧЕСКОЕ ОПИСАНИЕ

MODEL: 5234G3C-ESB-A

Примечание

1. Приведенные спецификации могут быть изменены без уведомления. BEELED сохраняет за собой право изменить материалы в приведенной выше спецификации.
2. При использовании светодиодов, максимально придерживайтесь данному описанию и инструкциям.

вышеперечисленных технических требований, инструкций и спцификаций.

3. Это техническое описание содержит материалы, защищенные авторским правом BEELED. Полная или частичная публикация без согласия BEELED запрещена.