



СВЕТОДИОДЫ BEELED – ТЕХНИЧЕСКОЕ ОПИСАНИЕ

Product Type: BLD-HP050UV3-E45

Version No.: 01

Product Description:

- 50 watt High Power LED
- Colloid Color: Transparent
- Emission Color: Purple
- Chip: 45mil Epileds
- Viewing Angle: 140°


Dice Material: GaInN



BEELED

СВЕТОДИОДЫ BEELED – ТЕХНИЧЕСКОЕ ОПИСАНИЕ

Outline Drawing



Notes:

1. All dimensions area in mm tolerance is $\pm 0.25\text{mm}$ unless otherwise noted.
2. An epoxy meniscus may extend about 1.2mm down the leads.
3. Burr around bottom of epoxy may be 0.5mm max.

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Items	Symbol	Maximum	Units
DC Forward Current	I_F	1500	mA
Peak forward current	I_{FP}	2500	mA
Reverse Voltage	V_R	50	V
Power consumption	P_D	50	W
Operation Temperature	T_{opr}	$-20 \sim +75$	$^\circ\text{C}$
Storage Temperature	T_{stg}	$-30 \sim +80$	$^\circ\text{C}$
Lead Soldering Temperature	T_{sol}	Max 260°C for 5 sec Max. (3mm from the base of the body)	

* Pulse width $\leq 0.1\text{msec}$ duty $\leq 1/10$



СВЕТОДИОДЫ BEELED – ТЕХНИЧЕСКОЕ ОПИСАНИЕ

Product Optical Properties (Ta = 25°C)

Item	Symbol	Conditions	Min	Averag	Max	Units
Forward Voltage	V_F	$I_F=1500\text{mA}$	30	e_{----}	34	V
	V_F	$I_F=2500\text{mA}$	30	-----	34	V
Reverse current	I_R	$V_R=50\text{V}$	---	-----	50	μA
Peak Wavelength	λ_p	$I_F=1500\text{mA}$	380	-----	390	nm
Chromaticity Coordinates	X	$I_F=1500\text{mA}$	-----	-----	---	----
	Y	$I_F=1500\text{mA}$	-----	-----	----	----
Luminous Flux	I_v	$I_F=1500\text{mA}$	300	----	400	lm
50% power Angle	$2\theta^{1/2}_{\text{H-H}}$	$I_F=1500\text{mA}$	---	70	---	deg
	$2\theta^{1/2}_{\text{V-V}}$	$I_F=1500\text{mA}$	----	---	---	deg

Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
		Purple	
DC Forward Current(mA)	If	1500	mA
Peak Pulse Current(mA)	If	2500	mA
Reverse Voltage	VR	50	V
LED Junction Temperature	Tj	125	°C
Operation Temperature	Topr	-20--65	°C
Storage Temperature	Tstg	-20--70	°C
Soldening Temperature	Tsol	260	°C
ESD Sensitivity	Vb	4000	V